

UL TL30x6 FIRE/BURGLARY SAFES



CONSTRUCTION

The UL TL30x6 is the next step above the TL-30 in security and protection. The Diamond Vault provides all the protection of the TL30 but takes it one step further by reinforcing the walls of the safe to give you superior six (6) sided protection against tool attacks. The Diamond Vault's composite body is a solid 3" thick and incorporates 18,000 PSI density concrete embodied with corundum aggregate and encased in a double layer of high-tensile steel. The door is 7" in overall thickness which includes 3" of solid barrier material.

PROTECTION

The Diamond Vault incorporates up to seven massive 2" chromed locking bolts, secured with two high-security, U.L. listed Group II combination locks. A huge floating glass plate "nerve center" covers the entire locking area. Additionally, the mechanism is protected by dual plates of tempered glass which will activate two randomly located re-locking devices in the event of a burglary attack. For ease of use the tri-spoke re-locker is adjustable and equipped with an internal captive cross lock which secures the re-locker bolt once it has fired.

DV-3020

Weight: 1900 • Cu.Ft.: 7.3 • Shelf: 2 Outside: 38"H X 28"W X 29.5"D • Inside: 30"H X 20"W X 18"D

DV-4524

Weight: 2800 • Cu.Ft.: 13.1 • Shelf: 3 Outside: 53"H X 32"W X 32.5"D • Inside: 45"H X 24"W X 21"D

DV-5524

Weight: 3250 • Cu.Ft.: 16 • Shelf: 4 Outside: 63"H X 32"W X 32.5"D • Inside: 55"H X 24"W X 21"D

DV-5534

Weight: 3600 • Cu.Ft.: 22.7 • Shelf: 4 Outside: 63"H X 42"W X 32.5"D • Inside: 55"H X 34"W X 21"D

DV-6034

Weight: 3950 • Cu.Ft.: 24.8 • Shelf: 5 Outside: 68"H X 42"W X 32.5"D • Inside: 60"H X 34"W X 21"D

DV-6528

Weight: 3800 • Cu.Ft.: 22.1 • Shelf: 5 Outside: 73"H X 36"W X 32.5"D • Inside: 65"H X 28"W X 21"D

DV-6836

Weight: 5000 • Cu.Ft.: 37 • Shelf: 5 Outside: 76"H X 44"W X 37.5"D • Inside: 68"H X 36"W X 26"D